









## **TECHNICAL SPECIFICATIONS**<sup>†</sup>

Length 2013 mm 1115 mm Wheel Base 1347 mm Ground Clearance 160 mm

Single Disc - 143 Kg, Double Disc - 144 Kg Kerb Weight

Seat Length 582 mm Seat Height 795 mm Fuel Tank Capacity 12 L

**ENGINE** 

4 Stroke, SI, BS-VI Engine

Displacement 162.71 cc

10.2 kW @ 8000 rpm Max Engine Output Max Torque 14.7 N-m @ 5500 rpm

PGM-FI Fuel System Bore x Stroke (mm) 57.300 x 63.096 Compression Ratio 10.0:1

Starting Method TRANSMISSION

Multiplate Wet Clutch Clutch Type No. of Gears 5 Gears

**TYRES & BRAKES** 

Tyre Size & Type (Front) 80/100-17 M/C 46P (Tubeless) 130/70-17 M/C 62P (Tubeless) Tyre Size & Type (Rear) Disc - 276 mm (Single Channel ABS) BrakeType & Size (Front) Brake Type & Size (Rear) Drum - 130 mm, Disc - 220 mm

Self/Kick

FRAME & SUSPENSION

Diamond Type Frame Type Front Suspension Telescopic Rear Suspension Hydraulic, Monoshock

ELECTRICALS

12V, 4.0 Ah Battery Headlamp







• +The technical specifications and design of the vehicle may vary according to the requirements and conditions without any notice • New X Blade meet Bharat Stage VI norms • Product shown in the picture may vary from actual product available in the market • Accessories shown in the picture are not part of standard equipment • All features may not be part of all variants • \*Figures as per internal testing • ^The Side Stand Indicator with Engine Cut Off adds to the safety of the rider, indicating when the stand is down and cutting off the ignition if the vehicle is put in gear in this situation

## Honda Motorcycle and Scooter India Pvt. Ltd.

Registered Office: Commercial Complex II, Sector - 49-50, Golf Course Extension Road, Gurugram - 122018 (Haryana), India Visit us at: www.honda2wheelersindia.com Customer Care: customercare@honda2wheelersindia.com

**Dealer Stamp** 

## Sharayu Honda Plot No. 79 Panvel Tel: 022-27492626/627/628 Mob: 9321629694 / 7021111677